



ORIGINAL VOC COMPLIANT

INDOOR FINISH MADE WITH RESIN-MODIFIED TUNG OIL



Protect your wood project with the trusted, go-to finish wood enthusiasts choose.

Easy to apply,
maintain
and restore

Enhances wood
grain and brings out its
inherent beauty

Available in
VOC 350 g/L
and 450 g/L

Available in
semi-gloss and
satin sheens



FAMILY
OWNED
SINCE 1910



Learn more at waterlox.com/original

Our ORIGINAL VOC Compliant Formula

Our ORIGINAL VOC Compliant formula is the same great product as our ORIGINAL formula, but is VOC compliant in all 50 states. It penetrates deep into wood to literally lock out water and provides a rich, distinctive finish that is easy to maintain.

PRODUCT DETAILS:

- A VOC compliant version of our ORIGINAL formula (available in 350 g/L and 450 g/L).
- Like all of our Tung Oil formulas, 90% of the resin portion of the formula is from renewable, natural resources.
- When used in conjunction with a Waterlox sealer, our ORIGINAL VOC Compliant formula penetrates deep into wood fibers to create a waterproof barrier while forming a protective yet elastic film that is durable against common household use and foot traffic.
- Easier to maintain than other interior clear or surface finishes.
- Non-toxic when dry and fully cured.
- Hand made in Ohio by a 4th generation, family-owned company.
- Available in semi-gloss and satin sheens.
- Available in gallon, quart and 2 ounce sizes.

PRODUCT USES & TIPS:

- Use on interior wood surfaces including floors, windows, doors, cabinetry, woodwork, tables, furniture, bar tops, picture frames, and various woodworking projects.
- Great on porous interior surfaces such as slate, brick, stone, tile, or cement to seal and prevent chalking and dusting*.
- Provides exceptional adhesion to oily, dense, exotic woods like teak, rosewood and ipe.
- One quart of ORIGINAL VOC Compliant sealer or finish covers 125 square feet per coat (500 square feet per coat for one gallon). One quart of the Universal Tung Oil Sealer covers 600-800 square feet per coat. No thinning required.
- Minimum dry time of 24 hours between coats. Poor ventilation, high humidity or cool temperatures may increase dry times.

* Once the project is completed, removing the finish can be very difficult as Waterlox will alter the appearance of porous substrates. Apply all intended coats to a small, inconspicuous area or scrap piece of substrate from the project and allow to dry properly prior to the actual application. Final color effect is always influenced by the texture, porosity, and by the method of application and will be difficult to reverse once finished. For slate, brick, stone and concrete, you may need only one coat to penetrate and seal.

1 First, apply ONE OF THESE products to create a waterproof seal.

ORIGINAL VOC SEALER & SEMI-GLOSS FINISH

OR UNIVERSAL TUNG OIL SEALER

PRODUCT #:
TB 6038



PRODUCT #:
TB 1000



2 Second, apply one of these products to build a protective and elastic finish.

ORIGINAL VOC SEALER & SEMI-GLOSS FINISH

PRODUCT #: **TB 6038**
GLOSS LEVEL: **50-55°**

This product is a finish and should be used as the 2nd and 3rd coats over the Waterlox Universal Tung Oil Sealer (TB 1000).



ORIGINAL VOC SATIN FINISH

PRODUCT #: **TB 6035 / 350 g/L**
PRODUCT #: **TB 6034 / 450 g/L**
GLOSS LEVEL: **20-25°**

This product is a finish and should be used as the 2nd and 3rd coats over the Waterlox Universal Tung Oil Sealer (TB 1000).



Premium tung oil finishes since 1910.