Printing date: 12/29/2016

Revision: 12/29/2016

#### **1** Identification

#### · Product identifier

- · Trade name: TRUETONE BUFF IN TUNG OIL FINISH
- Product code: TB 7011
- · Other means of identification: TRUETONE NATURAL
- · Recommended use and restriction on use
- · Recommended use: Wood stain
- · Restrictions on use: No relevant information available.

# • Details of the supplier of the Safety Data Sheet • Manufacturer/Supplier:

Waterlox Coatings Corporation 9808 Meech Avenue CLEVELAND, OH 44105 (216) 641-4877

#### • Emergency telephone number: ChemTel Inc. (800)255-3924, +1 (813)248-0585

## 2 Hazard(s) identification

## · Classification of the substance or mixture

Flam. Liq. 3 H226 Flammable liquid and vapor.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

#### · Label elements

#### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



#### · Signal word: Danger

#### · Hazard statements:

H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

- H372 Causes damage to the central nervous system through prolonged or repeated exposure.
- H304 May be fatal if swallowed and enters airways.

## · Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

(Cont'd. on page 2)

Printing date: 12/29/2016

Revision: 12/29/2016

# Trade name: TRUETONE BUFF IN TUNG OIL FINISH

	(Cont'd. of page 1
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P260	Do not breathe mist/vapors/spray.
P264	Wash thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection.
P240	Ground/bond container and receiving equipment.
P233	Keep container tightly closed.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing must not be allowed out of the workplace.
P303+P361+P	353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P370+P378	In case of fire: Use foam, powder, or carbon dioxide for extinction.
P363	Wash contaminated clothing before reuse.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P405	Store locked up.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/internationa regulations.

· Other hazards There are no other hazards not otherwise classified that have been identified.

# **3** Composition/information on ingredients

# · Chemical characterization: Mixtures

8052-41-3	Stoddard solvent	10-20%
	<ul> <li>Flam. Liq. 3, H226</li> <li>STOT RE 1, H372; Asp. Tox. 1, H304</li> </ul>	-
5989-27-5	d-limonene	1-5%
	<ul> <li>Flam. Liq. 3, H226</li> <li>Asp. Tox. 1, H304</li> <li>Skin Irrit. 2, H315; Skin Sens. 1, H317</li> <li>Eye Irrit. 2B, H320</li> </ul>	
556-67-2	octamethylcyclotetrasiloxane	1-5%
	<ul> <li>Flam. Liq. 3, H226</li> <li>Repr. 2, H361</li> </ul>	-
8007-24-7	Cashew Nutshell Oil	<1%
	<ul> <li>Eye Dam. 1, H318</li> <li>Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Skin Sens. 1A, H317</li> </ul>	
Additional	information:	
For the liste	ed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade (Contid	secret. I. on page 3

Printing date: 12/29/2016

Revision: 12/29/2016

(Cont'd. of page 2)

# Trade name: TRUETONE BUFF IN TUNG OIL FINISH

For the wording of the listed Hazard Statements refer to section 16.

# 4 First-aid measures

<ul> <li>Description of first aid measures</li> <li>After inhalation: Supply fresh air; consult doctor in case of complaints. Provide oxygen treatment if affected person has difficulty breathing.</li> </ul>
· After skin contact:
Immediately remove any clothing soiled by the product. Immediately wash with water and soap and rinse thoroughly.
If skin irritation is experienced, consult a doctor.
After eye contact:     Remove contact lenses if worn.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
· After swallowing:
Rinse out mouth and then drink plenty of water. Do not induce vomiting; immediately call for medical help.
A person vomiting while lying on their back should be turned onto their side.
• Most important symptoms and effects, both acute and delayed:
Headache Breathing difficulty
Coughing
Dizziness
Allergic reactions Cramp
Slight irritant effect on eyes.
Slight irritant effect on skin and mucous membranes.
Gastric or intestinal disorders when ingested.
Nausea in case of ingestion. Unconsciousness
· Danger:
Suspected of damaging fertility or the unborn child.
Causes damage to the central nervous system through prolonged or repeated exposure. <ul> <li>Indication of any immediate medical attention and special treatment needed:</li> </ul>
If swallowed or in case of vomiting, danger of entering the lungs.
Medical supervision for at least 48 hours.
If necessary oxygen respiration treatment. Monitor circulation, possible shock treatment.
Later observation for pneumonia and pulmonary edema.
Contains d-limonene, Cashew Nutshell Oil. May produce an allergic reaction.
Treat skin and mucous membrane with antihistamine and corticoid preparations.

# **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Foam

(Cont'd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 12/29/2016

Revision: 12/29/2016

#### Trade name: TRUETONE BUFF IN TUNG OIL FINISH

(Cont'd. of page 3)

Fire-extinguishing powder Carbon dioxide Gaseous extinguishing agents Water fog / haze • For safety reasons unsuitable extinguishing agents: Water stream. Water spray • Special bazards arising from the substance or u

- Special hazards arising from the substance or mixture Flammable liquid and vapor.
   Formation of toxic gases is possible during heating or in case of fire.
   Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device. Wear fully protective suit.
   Additional information: Eliminate all ignition sources if safe to do so.

Cool endangered containers with water fog.

# 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures For large spills, use respiratory protective device against the effects of fumes/dust/aerosol. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources. Protect from heat. Particular danger of slipping on leaked/spilled product. Environmental precautions Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course or sewage system. Prevent from spreading (e.g. by damming-in or oil barriers). Methods and material for containment and cleaning up Allow to solidify. Pick up mechanically. Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Remove from the water surface (e.g. skim or suck off). Send for recovery or disposal in suitable receptacles. Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and storage

- · Handling
- · Precautions for safe handling:

Prevent formation of aerosols. Use only in well ventilated areas.

(Cont'd. on page 5)

rinting date: 12/29	/2016	Revision: 12/29/2010
rade name: TRI	JETONE BUFF IN TUNG OIL FINISH	
		(Cont'd. of page 4
Avoid contact v	vith the eyes and skin.	
Keep out of rea		
	pout protection against explosions and fires:	
	ources away - Do not smoke.	
	electrostatic charges.	
	ry protective device available. s-air mixtures may be formed in empty containers/rece	ntaclas
-		
	or safe storage, including any incompatibilitie	S
Storage		
	to be met by storerooms and receptacles:	
Store in a cool	tion for receptacles.	
	near extreme heat, ignition sources or open flame.	
	bout storage in one common storage facility:	
Store away from		
Store away fror	n oxidizing agents.	
Further inform	nation about storage conditions: Store in cool, dry co	onditions in well sealed receptacles.
· Specific end	use(s) No relevant information available.	
8 Exposure co	ontrols/personal protection	
-	ontrols/personal protection	
· Control para	meters	
· Control para	· · ·	kplace:
· Control para	meters with limit values that require monitoring at the wor	kplace:
Control para	meters with limit values that require monitoring at the wor	kplace:
Control para Components v 8052-41-3 Stor	meters with limit values that require monitoring at the wor ddard solvent	kplace:
Control para     Components     8052-41-3 Store     PEL (USA)	meters with limit values that require monitoring at the work ddard solvent Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup>	kplace:
Control para     Components     8052-41-3 Store     PEL (USA)	meters with limit values that require monitoring at the work ddard solvent Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm Long-term value: 350 mg/m <sup>3</sup>	kplace:
Control para     Components     8052-41-3 Store     PEL (USA)	meters with limit values that require monitoring at the work ddard solvent Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup>	kplace:
Control para     Components v 8052-41-3 Store PEL (USA) REL (USA)	meters with limit values that require monitoring at the work ddard solvent Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup> *15-min Long-term value: 525 mg/m <sup>3</sup> , 100 ppm Short-term value: 580 mg/m <sup>3</sup>	kplace:
Control para     Components v 8052-41-3 Stoc PEL (USA) REL (USA) TLV (USA)	meters with limit values that require monitoring at the work ddard solvent Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup> *15-min Long-term value: 525 mg/m <sup>3</sup> , 100 ppm	kplace:
Control para     Components v 8052-41-3 Stoc PEL (USA) REL (USA) TLV (USA)	meters with limit values that require monitoring at the work ddard solvent Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup> *15-min Long-term value: 525 mg/m <sup>3</sup> , 100 ppm Short-term value: 580 mg/m <sup>3</sup>	kplace:
Control para     Components v 8052-41-3 Store PEL (USA) REL (USA) TLV (USA) EL (Canada) EV (Canada)	meters with limit values that require monitoring at the work ddard solvent Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup> *15-min Long-term value: 525 mg/m <sup>3</sup> , 100 ppm Short-term value: 580 mg/m <sup>3</sup> Long-term value: 290 mg/m <sup>3</sup>	kplace:
Control para     Components v 8052-41-3 Store PEL (USA) REL (USA) TLV (USA) EL (Canada) EV (Canada) LMPE (Mexico)	meters with limit values that require monitoring at the worl ddard solvent Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup> *15-min Long-term value: 525 mg/m <sup>3</sup> , 100 ppm Short-term value: 580 mg/m <sup>3</sup> Long-term value: 290 mg/m <sup>3</sup> Long-term value: 525 mg/m <sup>3</sup>	kplace:
Control para     Components v 8052-41-3 Store PEL (USA) REL (USA) TLV (USA) EL (Canada) EV (Canada) LMPE (Mexico)	meters with limit values that require monitoring at the work ddard solvent Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup> *15-min Long-term value: 525 mg/m <sup>3</sup> , 100 ppm Short-term value: 580 mg/m <sup>3</sup> Long-term value: 290 mg/m <sup>3</sup> Long-term value: 525 mg/m <sup>3</sup> ) Long-term value: 525 mg/m <sup>3</sup>	kplace:
Control para     Components v 8052-41-3 Store PEL (USA) REL (USA) TLV (USA) EL (Canada) EV (Canada) EV (Canada) LMPE (Mexico) 556-67-2 octar WEEL (USA)	meters         with limit values that require monitoring at the worl         ddard solvent         Long-term value: 2900 mg/m³, 500 ppm         Long-term value: 350 mg/m³         Ceiling limit value: 1800* mg/m³         *15-min         Long-term value: 525 mg/m³, 100 ppm         Short-term value: 580 mg/m³         Long-term value: 525 mg/m³         Long-term value: 525 mg/m³         Long-term value: 525 mg/m³         Long-term value: 100 ppm         methylcyclotetrasiloxane         Long-term value: 10* ppm         *OARS WEEL	kplace:
Control para     Components v 8052-41-3 Store PEL (USA) REL (USA) TLV (USA) EL (Canada) EV (Canada) LMPE (Mexico) 556-67-2 octar WEEL (USA)	meters with limit values that require monitoring at the worl ddard solvent Long-term value: 2900 mg/m³, 500 ppm Long-term value: 350 mg/m³ Ceiling limit value: 1800* mg/m³ *15-min Long-term value: 525 mg/m³, 100 ppm Short-term value: 525 mg/m³ Long-term value: 290 mg/m³ Long-term value: 525 mg/m³ ) Long-term value: 525 mg/m³ ) Long-term value: 100 ppm methylcyclotetrasiloxane Long-term value: 10* ppm *OARS WEEL ntrols	kplace:
Control para     Components v     8052-41-3 Store     PEL (USA)     REL (USA)     TLV (USA)     EL (Canada)     EV (Canada)     LMPE (Mexico)     556-67-2 octar     WEEL (USA)      Exposure co     Personal prote	meters with limit values that require monitoring at the worl ddard solvent Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup> *15-min Long-term value: 525 mg/m <sup>3</sup> , 100 ppm Short-term value: 525 mg/m <sup>3</sup> Long-term value: 290 mg/m <sup>3</sup> Long-term value: 525 mg/m <sup>3</sup> Long-term value: 525 mg/m <sup>3</sup> Long-term value: 100 ppm methylcyclotetrasiloxane Long-term value: 10* ppm *OARS WEEL ntrols ective equipment:	kplace:
Control para     Components v     8052-41-3 Store     PEL (USA)     REL (USA)     TLV (USA)     EL (Canada)     EV (Canada)     LMPE (Mexico)     556-67-2 octar     WEEL (USA)      Exposure co     Personal protein	meters with limit values that require monitoring at the worl ddard solvent Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup> *15-min Long-term value: 525 mg/m <sup>3</sup> , 100 ppm Short-term value: 525 mg/m <sup>3</sup> Long-term value: 580 mg/m <sup>3</sup> Long-term value: 525 mg/m <sup>3</sup> Long-term value: 525 mg/m <sup>3</sup> Long-term value: 100 ppm methylcyclotetrasiloxane Long-term value: 10* ppm *OARS WEEL ntrols ective equipment: ctive and hygienic measures:	
Control para     Components v     8052-41-3 Store     PEL (USA)     REL (USA)     TLV (USA)     EL (Canada)     EV (Canada)     LMPE (Mexico)     556-67-2 octar     WEEL (USA)      Exposure co     Personal protect     The usual prece	meters         with limit values that require monitoring at the worl         ddard solvent         Long-term value: 2900 mg/m³, 500 ppm         Long-term value: 350 mg/m³         Ceiling limit value: 1800* mg/m³         *15-min         Long-term value: 525 mg/m³, 100 ppm         Short-term value: 580 mg/m³         Long-term value: 525 mg/m³         Long-term value: 100 ppm         methylcyclotetrasiloxane         Long-term value: 10* ppm         *OARS WEEL         ntrols         ective equipment:         ctive and hygienic measures:         autionary measures for handling chemicals should be	
Control para     Components v 8052-41-3 Store PEL (USA) REL (USA)  TLV (USA) EL (Canada) EV (Canada) LMPE (Mexico) 556-67-2 octar WEEL (USA)      Exposure co Personal protect The usual precete Keep away from	meters with limit values that require monitoring at the worl ddard solvent Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup> *15-min Long-term value: 525 mg/m <sup>3</sup> , 100 ppm Short-term value: 525 mg/m <sup>3</sup> Long-term value: 580 mg/m <sup>3</sup> Long-term value: 525 mg/m <sup>3</sup> Long-term value: 525 mg/m <sup>3</sup> Long-term value: 100 ppm methylcyclotetrasiloxane Long-term value: 10* ppm *OARS WEEL ntrols ective equipment: ctive and hygienic measures:	
Control para     Components v 8052-41-3 Store PEL (USA) REL (USA)  TLV (USA) EL (Canada) EV (Cana	meters         with limit values that require monitoring at the worl         ddard solvent         Long-term value: 2900 mg/m³, 500 ppm         Long-term value: 350 mg/m³         Ceiling limit value: 1800* mg/m³         *15-min         Long-term value: 525 mg/m³, 100 ppm         Short-term value: 525 mg/m³         Long-term value: 520 mg/m³         Long-term value: 525 mg/m³         Long-term value: 525 mg/m³         Long-term value: 100 ppm         methylcyclotetrasiloxane         Long-term value: 100 ppm         *OARS WEEL         ntrols         ective equipment:         ctive and hygienic measures:         autionary measures for handling chemicals should be for foodstuffs, beverages and feed.         move all soiled and contaminated clothing.         efore breaks and at the end of work.	
Control para     Components v 8052-41-3 Store PEL (USA) REL (USA)  TLV (USA) EL (Canada) EV (Canada) EV (Canada) LMPE (Mexico) 556-67-2 octar WEEL (USA)      Exposure co Personal prote General prote The usual prec Keep away from Immediately ref Wash hands be Do not inhale g	meters         with limit values that require monitoring at the worl         ddard solvent         Long-term value: 2900 mg/m³, 500 ppm         Long-term value: 350 mg/m³         Ceiling limit value: 1800* mg/m³         *15-min         Long-term value: 525 mg/m³, 100 ppm         Short-term value: 525 mg/m³         Long-term value: 100 ppm         methylcyclotetrasiloxane         Long-term value: 10° ppm         *OARS WEEL         ntrols         ective equipment:         ctive and hygienic measures:         autionary measures for handling chemicals should be in foodstuffs, beverages and feed.         move all soiled and contaminated clothing.         efore breaks and at the end of work.         ases / fumes / aerosols.	
Control para     Components v 8052-41-3 Store PEL (USA) REL (USA)  TLV (USA) EL (Canada) EV (Canada) EV (Canada) LMPE (Mexico) 556-67-2 octar WEEL (USA)      Exposure co Personal prote General prote The usual prec Keep away from Immediately ref Wash hands be Do not inhale g	meters         with limit values that require monitoring at the worl         ddard solvent         Long-term value: 2900 mg/m³, 500 ppm         Long-term value: 350 mg/m³         Ceiling limit value: 1800* mg/m³         *15-min         Long-term value: 525 mg/m³, 100 ppm         Short-term value: 525 mg/m³         Long-term value: 520 mg/m³         Long-term value: 525 mg/m³         Long-term value: 525 mg/m³         Long-term value: 100 ppm         methylcyclotetrasiloxane         Long-term value: 100 ppm         *OARS WEEL         ntrols         ective equipment:         ctive and hygienic measures:         autionary measures for handling chemicals should be for foodstuffs, beverages and feed.         move all soiled and contaminated clothing.         efore breaks and at the end of work.	

Printing date: 12/29/2016 Trade name: TRUETONE BUFF IN TUNG OIL FINISH (Cont'd. of page 5) Pregnant women should strictly avoid inhalation or skin contact. · Engineering controls: No relevant information available. · Breathing equipment: Not required under normal conditions of use. Use suitable respiratory protective device in case of insufficient ventilation. Use suitable respiratory protective device when aerosol or mist is formed. For spills, respiratory protection may be advisable. Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. · Eye protection: Safety glasses · Body protection: Protective work clothing · Limitation and supervision of exposure into the environment No relevant information available.

Physical and chemical prop	
Information on basic physical	and chemical properties
Appearance:	
Form:	Liquid
Color:	Amber colored
· Odor:	Petroleum-like
Odor threshold:	Not determined.
· pH-value:	Not determined.
• Melting point/Melting range:	Not determined.
<ul> <li>Boiling point/Boiling range:</li> </ul>	150 - 199 °C (302 - 390 °F)
Flash point:	>38 °C (>100 °F)
· Flammability (solid, gaseous):	Not applicable.
• Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.
Explosion limits	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	>1 (Air=1)

Revision: 12/29/2016

Printing date: 12/29/2016

Revision: 12/29/2016

#### Trade name: TRUETONE BUFF IN TUNG OIL FINISH

		(Cont'd. of page 6
· Density:		
Relative density:	0.91	
Vapor density:	Not determined.	
Evaporation rate:	Not determined.	
· Solubility in / Miscibility with		
Water:	Insoluble.	
· Partition coefficient (n-octanol/wa	ater): Not determined.	
· Viscosity		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
VOC content:	191 g/L	
· Other information	No relevant information available.	

## 10 Stability and reactivity

- · Reactivity: No relevant information available.
- Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided: Keep away from heat and direct sunlight.
- **Possibility of hazardous reactions** Combustible liquid.
- Reacts with strong acids and oxidizing agents.

Toxic fumes may be released if heated above the decomposition point.

Reacts with catalysts.

#### • **Conditions to avoid** Keep ignition sources away - Do not smoke. Store away from oxidizing agents.

- · Incompatible materials Oxidizers
- Hazardous decomposition products Carbon monoxide and carbon dioxide Hydrocarbons

## **11 Toxicological information**

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

#### 5989-27-5 d-limonene

Oral LD50 4400 mg/kg (rat)

- · Primary irritant effect:
- On the skin: Slight irritant effect on skin and mucous membranes.
- · On the eye: Slight irritant effect on eyes.
- · Sensitization: Sensitization possible through skin contact.

(Cont'd. on page 8)

Revision: 12/29/2016

# Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

	(Cont'd. of page
· Carcinogenic categories	
· IARC (International Agency for Research on Cancer):	
Present in trace quantities.	
100-41-4 ethylbenzene	2E
91-20-3 naphthalene	28
• NTP (National Toxicology Program):	
Present in trace quantities.	
91-20-3 naphthalene	F
· OSHA-Ca (Occupational Safety & Health Administration):	
None of the ingredients are listed.	
· Probable route(s) of exposure:	
Ingestion.	
Inhalation.	
Eye contact.	
Skin contact.	
· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)	
Repr. 2	
• Germ cell mutagenicity: Based on available data, the classification criteria are not me	t.
• Carcinogenicity: Based on available data, the classification criteria are not met.	
• Reproductive toxicity: Suspected of damaging fertility or the unborn child.	
• STOT-single exposure: Based on available data, the classification criteria are not met	
· STOT-repeated exposure:	
Causes damage to the central nervous system through prolonged or repeated exposure	રે.
• Aspiration hazard: May be fatal if swallowed and enters airways.	

· Toxicity

Printing date: 12/29/2016

- · Aquatic toxicity Harmful to aquatic life with long lasting effects.
- · Persistence and degradability No relevant information available.
- Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available.
- · Ecotoxical effects:
- **Remark:** Due to mechanical actions of the product (e.g. agglutinations), damages may occur.
- · Additional ecological information
- · General notes: Do not allow product to reach ground water, water course or sewage system.
- · Other adverse effects No relevant information available.

(Cont'd. on page 9)

Printing date: 12/29/2016

#### Trade name: TRUETONE BUFF IN TUNG OIL FINISH

(Cont'd. of page 8)

## 13 Disposal considerations

#### · Waste treatment methods

#### · Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

## · Uncleaned packagings

• Recommendation: Disposal must be made according to official regulations.

4 Transport information	
	Not regulated. TUS DOT regulations. Labeling is only required for single packages mbustible symbol and Proper Shipping Name.
· ADR, IMDG, IATA	UN1263
· UN proper shipping name · DOT	Not regulated.
· ADR · IMDG · IATA	PAINT, ENVIRONMENTALLY HAZARDOUS PAINT, MARINE POLLUTANT Paint
· Transport hazard class(es)	
· DOT · Class	Not regulated.
· ADR	
· Class · Label	3 (F1) Flammable liquids
· IMDG	ى ى
· Class	3 Flammable liquids
	(Cont'd. on page 1)

Printing date: 12/29/2016

Revision: 12/29/2016

# Trade name: TRUETONE BUFF IN TUNG OIL FINISH

	(Cont'd. of page
· Label	3
· Class · Label	3 Flammable liquids 3
· Packing group · DOT · ADR, IMDG, IATA	Not regulated. III
Environmental hazards Marine pollutant:	Product contains environmentally hazardous substances: d-limonene, octamethylcyclotetrasiloxane Symbol (fish and tree)
Special precautions for user Danger code (Kemler): EMS Number: Segregation groups	Warning: Flammable liquids 30 F-E, <u>S-E</u> Liquid halogenated hydrocarbons
Transport in bulk according to Ann MARPOL73/78 and the IBC Code	ex II of Not applicable.
Transport/Additional information:	
DOT	Product is additionally classified as a MARINE POLLUTANT based on MARPOL and DOT rules. Labeling as a MARINE POLLUTANT is not required for non-bulk single package shipments by motor vehicle rail car or aircraft. Bulk packaging consists of maximum capacity of greater than 450L (119 gallons for a liquid and a maximum net mass greater tha 400kg (882 pounds) for a solid.
ADR	
Limited Quantity for packages les	s than 30 kg gross and inner packagings less than 5 L each.
IMDG	
Limited Quantity for packages les	s than 30 kg gross and inner packagings less than 5 L each.
-	

# Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 12/29/2016

Revision: 12/29/2016

## Trade name: TRUETONE BUFF IN TUNG OIL FINISH

(Cont'd. of page 10)

# $\cdot$ IATA



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each / 10 L net.

# 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the sul	ostance or
mixture	
· United States (USA)	

·SARA

· Section 302 (extremely hazardous substances):

None of the ingredients are listed.

## Section 304 (emergency release notification):

None of the ingredients are listed.

#### Section 355 (extremely hazardous substances):

None of the ingredients are listed.

#### Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

#### · TSCA (Toxic Substances Control Act)

All ingredients are listed.

## Proposition 65 (California)

· Chemicals known to cause cancer:

# Present in trace quantities.

91-20-3 naphthalene

# 100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

#### · Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

#### · Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

#### · EPA (Environmental Protection Agency):

None of the ingredients are listed.

## · IARC (International Agency for Research on Cancer):

Present in trace quantities.

100-41-4 ethylbenzene 91-20-3 naphthalene 2B 2B

(Cont'd. on page 12)

Printing date: 12/29/2016

Revision: 12/29/2016

Trade name: TRUETONE BUFF IN TUNG OIL FINISH

(Cont'd. of page 11)

#### · NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

# **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Date of preparation / last revision 12/29/2016 / -

#### Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety **OSHA: Occupational Safety & Health** TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL: Recommended Exposure Limit** LDLo: Lowest Lethal Dose Observed Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Repr. 2: Reproductive toxicity - Category 2 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 Asp. Tox. 1: Aspiration hazard - Category 1 Sources Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets, Individual Manufacturers SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com